



ACTIVE SAFETY

Max Speed 158 ft/min 0,8 m/s	32 - 176 °F 0 - 80 °C	N₂	P max 1595 psi 110 bar	P min 290 psi 20 bar	S 3.55 in ² 22,9 cm ²	
---	--------------------------	----------------------	-------------------------------------	-----------------------------------	--	--

PART NUMBER	F ₀ Initial Force		C _u		L		B		T		 ~ lb ~ Kg	
	ton	daN	inch	mm	inch	mm	inch	mm	inch	mm		
CB 2500 - 025 - A	2.52	2520	0.98	25	2.64	67	0.91	23	1.69	43	2.83	1,28
CB 2500 - 038 - A			1.50	38	3.15	80	1.42	36	1.97	50	3.10	1,41
CB 2500 - 050 - A			1.97	50	3.62	92	1.89	48	2.44	62	3.35	1,52
CB 2500 - 075 - A			2.95	75	4.61	117	2.87	73	3.43	87	3.87	1,75
CB 2500 - 100 - A			3.94	100	5.59	142	3.86	98	4.41	112	4.38	1,99
CB 2500 - 150 - A			5.91	150	7.56	192	5.83	148	6.38	162	5.42	2,46

CB

HOW TO ORDER p. 39	ACCESSORIES p. 47	SERVICE TOOLS p. 68 Part Number 58UT051A or 58UT054A	MAINTENANCE KIT Part Number 39BMCC01000A
------------------------------	-----------------------------	--	--