



ACTIVE SAFETY

Max Speed 158 ft/min 0,8 m/s	32 - 176 °F 0 - 80 °C	N₂	P max 1595 psi 110 bar	P min 290 psi 20 bar	S 1.491 in ² 9,62 cm ²	
---	--------------------------	----------------------	-------------------------------------	-----------------------------------	---	--

PART NUMBER	F ₀ Initial Force		C _u		L		L min			
	ton	daN	inch	mm	inch	mm	inch	mm	~ lb	~ Kg
CC 1000 - 025 - A	1.06	1060	0.98	25	2.89	73,5	1.91	48,5	1,91	0,87
CC 1000 - 038 - A			1.5	38	3.92	99,5	2.42	61,5	2,31	1,050
CC 1000 - 050 - A			1.97	50	4.86	123,5	2.89	73,5	2,68	1,217
CC 1000 - 075 - A			2.95	75	6.83	173,5	3.88	98,5	3,45	1,567
CC 1000 - 100 - A			3.94	100	8.80	223,5	4.86	123,5	4,22	1,916
CC 1000 - 150 - A			5.91	150	12.74	323,5	6.83	173,5	5,77	2,615

CC

HOW TO ORDER p. 43	ACCESSORIES p. 47	SERVICE TOOLS p. 68 Part Number 58UT051A or 58UT054A	MAINTENANCE KIT Part Number 39BMCC01000A
------------------------------	-----------------------------	--	--