



**ACTIVE SAFETY**



**CR**

<b>Max Speed</b> 315 ft/min 1.6 m/s	32 - 176 °F 0 - 80 °C	<b>N<sub>2</sub></b>	<b>P max</b> 2175 psi 150 bar	<b>P min</b> 363 psi 25 bar	<b>S</b> 10.987 in <sup>2</sup> 70.88 cm <sup>2</sup>	
---	--------------------------	----------------------	-------------------------------------	-----------------------------------	---	--

PART NUMBER	F <sub>0</sub> Initial Force		Cu		L		L min			
	inch	mm	inch	mm	inch	mm	inch	mm	~ lb	~ Kg
CR 10700 - 100 - A	8.91 ton - 8910 daN	10.69 ton - 10690 daN	3.94	100	5.31	135	1.38	35	25.13	11.40
CR 10700 - 125 - A			4.92	125	7.28	185	2.36	60	30.98	14.05
CR 10700 - 160 - A			6.30	160	10.04	255	3.74	95	39.61	17.97
CR 10700 - 200 - A			7.87	200	13.19	335	5.31	135	44.74	20.29
CR 10700 - 250 - A			9.84	250	17.13	435	7.28	185	53.92	24.46

<b>HOW TO ORDER</b> p. 17	<b>ACCESSORIES</b> p. 47	<b>SERVICE TOOLS</b> p. 68 Part Number 58UT049A	<b>MAINTENANCE KIT</b> Part Number 39BMCR10700A
------------------------------	-----------------------------	--	--