



CR

Max Speed 315 ft/min 1.6 m/s	32 - 176 °F 0 - 80 °C	N ₂	P max 2175 psi 150 bar	P min 363 psi 25 bar	S 5.143 in ² 33.18 cm ²	
-------------------------------------------	--------------------------	----------------	-------------------------------------	-----------------------------------	------------------------------------------------------------	--

PART NUMBER	F ₀ Initial Force		Cu		L		L min			
	inch	mm	inch	mm	inch	mm	inch	mm	~ lb	~ Kg
CR 5200 - 100 - A	4.37 ton - 4370 daN	5.24 ton - 5240 daN	3.94	100	5.31	135	1.38	35	11.20	5,08
CR 5200 - 125 - A	1813 psi 125 bar	2175 psi 150 bar	4.92	125	7.28	185	2.36	60	13.21	5,99
CR 5200 - 160 - A			6.30	160	10.04	255	3.74	95	16.01	7,26
CR 5200 - 200 - A			7.87	200	13.19	335	5.31	135	19.22	8,72

HOW TO ORDER p. 17	ACCESSORIES p. 47	SERVICE TOOLS p. 68 Part Number 58UT047A	MAINTENANCE KIT Part Number 39BMCR05000A
------------------------------	-----------------------------	----------------------------------------------------	----------------------------------------------------