



P*		E min		G min	
psi	bar	inch	mm	inch	mm
1500	103	2.38	60	1.25	32
2000	138	2.75	70	1.43	37

P* = Charging pressure



ACTIVE SAFETY



CRD

Max Speed 315 ft/min 1,6 m/s	32 - 176 °F 0 - 80 °C	N ₂	P max 2000 psi 138 bar	P min 363 psi 25 bar	S 1.491 in ² 9,62 cm ²	
---	--------------------------	----------------	-------------------------------------	-----------------------------------	---	--

PART NUMBER	F ₀ Initial Force		C _u		L		B		T*min		T**min		~lb ~ Kg	
	1 ton 1000 daN	1.5 ton 1500 daN	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm		
CRD 1500 - 1.00 - A			1.00	25,4	2.66	67,6	0.97	24,6	1.73	44,0	1.93	49,0	1.82	0,83
CRD 1500 - 1.50 - A			1.50	38,1	3.16	80,3	1.47	37,3	1.89	48,0	2.09	53,0	2.05	0,93
CRD 1500 - 2.00 - A			2.00	50,8	3.66	93,0	1.97	50,0	2.36	60,0	2.56	65,0	2.28	1,03
CRD 1500 - 2.50 - A			2.50	63,5	4.16	105,7	2.47	62,7	2.87	73,0	3.07	78,0	2.51	1,14
CRD 1500 - 3.00 - A			3.00	76,2	4.66	118,4	2.97	75,4	3.39	86,0	3.58	91,0	2.74	1,24
CRD 1500 - 3.50 - A			3.50	88,9	5.16	131,1	3.47	88,1	3.86	98,0	4.06	103,0	2.97	1,35
CRD 1500 - 4.00 - A			4.00	101,6	5.66	143,8	3.97	100,8	4.37	111,0	4.57	116,0	3.20	1,45
CRD 1500 - 4.50 - A			4.50	114,3	6.16	156,5	4.47	113,5	4.88	124,0	5.08	129,0	3.43	1,56
CRD 1500 - 5.00 - A			5.00	127,0	6.66	169,2	4.97	126,2	5.39	137,0	5.55	141,0	3.66	1,66

T* = 1500 psi/103 bar T** = 2000 psi/138 bar

HOW TO ORDER p. 27	ACCESSORIES p. 47	SERVICE TOOLS p. 68 Part Number 58UT045A	MAINTENANCE KIT Part Number 39BMCR01500A
------------------------------	-----------------------------	--	--