



P*		E min		G min	
psi	bar	inch	mm	inch	mm
1500	103	3.75	95	2.13	54
2000	138	4.50	115	2.44	62

P\* = Charging pressure



**ACTIVE SAFETY**



**CRD**

<b>Max Speed</b> 315 ft/min 1,6 m/s	32 - 176 °F 0 - 80 °C	N <sub>2</sub>	<b>P max</b> 2000 psi 138 bar	<b>P min</b> 363 psi 25 bar	<b>S</b> 5.143 in <sup>2</sup> 33,18 cm <sup>2</sup>	
---	--------------------------	----------------	-------------------------------------	-----------------------------------	--	--

PART NUMBER	Fo Initial Force	Cu		L		B		T*min		T**min		~ lb ~ Kg	
		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm		
CRD 5000 - 1.00 - A	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>4 ton 4000 daN</p> </div> <div style="text-align: center;"> <p>5 ton 5000 daN</p> </div> </div>	1.00	25,4	2.66	67,6	1.50	38,1	2.52	64,0	2.76	70,0	6.17	2,80
CRD 5000 - 1.50 - A		1.50	38,1	3.16	80,3	2.00	50,8	2.76	70,0	2.99	76,0	6.84	3,10
CRD 5000 - 2.00 - A		2.00	50,8	3.66	93	2.50	63,5	3.27	83,0	3.50	89,0	7.51	3,41
CRD 5000 - 2.50 - A		2.50	63,5	4.16	105,7	3.00	76,2	3.74	95,0	4.02	102,0	8.18	3,71
CRD 5000 - 3.00 - A		3.00	76,2	4.66	118,4	3.50	88,9	4.25	108,0	4.49	114,0	8.85	4,01
CRD 5000 - 3.50 - A		3.50	88,9	5.16	131,1	4.00	101,6	4.76	121,0	5.00	127,0	9.52	4,32
CRD 5000 - 4.00 - A		4.00	101,6	5.66	143,8	4.50	114,3	5.24	133,0	5.51	140,0	10.19	4,62
CRD 5000 - 4.50 - A		4.50	114,3	6.16	156,5	5.00	127,0	5.75	146,0	5.98	152,0	10.86	4,93
CRD 5000 - 5.00 - A		5.00	127,0	6.66	169,2	5.50	139,7	6.26	159,0	6.50	165,0	11.53	5,23
CRD 5000 - 5.50 - A		5.50	139,7	7.16	181,9	6.00	152,4	6.73	171,0	7.01	178,0	12.20	5,53
CRD 5000 - 6.00 - A		6.00	152,4	7.66	194,6	6.50	165,1	7.24	184,0	7.52	191,0	12.87	5,84
CRD 5000 - 6.50 - A		6.50	165,1	8.16	207,3	7.00	177,8	7.76	197,0	7.99	203,0	13.54	6,14
CRD 5000 - 7.00 - A		7.00	177,8	8.66	220,0	7.50	190,5	8.27	210,0	8.50	216,0	14.21	6,45

T\* = 1500 psi/103 bar    T\*\* = 2000 psi/138 bar

<b>HOW TO ORDER</b> p. 27	<b>ACCESSORIES</b> p. 47	<b>SERVICE TOOLS</b> p. 68 Part Number 58UT047A	<b>MAINTENANCE KIT</b> Part Number 39BMCR05000A
------------------------------	-----------------------------	--	--