

Il nuovo codice sarà fornito solo ad esaurimento del vecchio

The new code will be supplied only when the old will be out of stock

Der neue Kode wird nur angegeben, wenn der alte nicht mehr lieferbar ist

Le nouveau code sera fourni uniquement lorsque le vieux stock sera écoulé

El nuevo código será suministrado sólo cuando se agoten las existencias del antiguo


O novo código irá ser fornecido apenas quando o antigo esgotar stock

* $F_{1i} =$

Isothermal end force at 100% Cu

** $F_{1p} =$

Polytropic end force at 100% Cu



ACTIVE SAFETY



OSAS



USAS



OPAS



SKUDO

N ₂		0 - 80 °C 32 - 176 °F	ΔP ± 0,33 %/°C	P max 180 bar 2610 psi	P min 20 bar 290 psi	S 1,77 cm ² 0,27 in ²	SPM ~ 40 - 100 (at 20°C)	Max Speed 1,8 m/s 70.8 in/s	Maintenance kit Disposable
CODE	Cu	L	L min	F ₀	F _{1i} *	F _{1p} **	V ₀	PED 2014/68/EU	
PHASING OUT from 01/2020	NEW	mm inch	mm inch	mm inch	daN lb	daN lb	cm ³ in ³	~Kg ~lb	~lb
RS 320 - 007 - B	RS 320 - 007 - C	7 0.28	50 1.97	43 1.69	320 719 ± 5%	438 985	5,5 0.34	0,10 0.23	✓
RS 320 - 010 - B	RS 320 - 010 - C	10 0.39	56 2.20	46 1.81		463 1041	6,9 0.42	0,11 0.24	✓
RS 320 - 012 - B	RS 320 - 012 - C	12 0.47	60 2.36	48 1.89		475 1069	7,8 0.47	0,11 0.25	✓
RS 320 - 016 - B	RS 320 - 016 - C	16 0.63	68 2.68	52 2.05		495 1112	9,6 0.58	0,12 0.26	✓
RS 320 - 022 - B	RS 320 - 022 - C	22 0.87	80 3.15	58 2.28		514 1155	12,3 0.75	0,13 0.29	✓
RS 320 - 029 - B	RS 320 - 029 - C	29 1.14	94 3.70	65 2.56		529 1189	15,5 0.94	0,14 0.31	✓
RS 320 - 035 - B	RS 320 - 035 - C	35 1.38	106 4.17	71 2.80		538 1209	18,2 1.11	0,15 0.33	✓
RS 320 - 047 - B	RS 320 - 047 - C	47 1.85	130 5.12	83 3.27		550 1237	23,6 1.44	0,17 0.38	✓
RS 320 - 060 - B	RS 320 - 060 - C	60 2.36	156 6.14	96 3.78		559 1256	29,5 1.80	0,19 0.43	✓
RS 320 - 072 - B	RS 320 - 072 - C	72 2.83	185 7.28	113 4.45		557 1252	35,5 2.17	0,22 0.48	✓
RS 320 - 077 - B	RS 320 - 077 - C	77 3.03	195 7.68	118 4.65	559 1257	37,7 2.30	0,23 0.50	✓	
RS 320 - 097 - B	RS 320 - 097 - C	97 3.82	235 9.25	138 5.43	566 1272	46,8 2.85	0,26 0.57	✓	
RS 320 - 122 - B	RS 320 - 122 - C	122 4.80	285 11.22	163 6.42	571 1284	58,1 3.54	0,30 0.66	✓	

**WARNING
REMOVE SKUDO**

Upside down mounting

FC / FCC fixings

Drop-in

Bottom mount

FC 25 B
FCC 25 A

FS3 25

HOW TO ORDER

☞ p. 73

INSTALLATION GUIDELINE

☞ p. 205